CONTRACT SERVICES Pty Ltd Industrial Division

Global's Industrial Division is highly experienced in the construction of polyethylene pipe lines and pipe systems, including outfall and intake submarine lines, general polyethylene fabrication works and manufacture of polyethylene products. Other works involve designing and installing Industrial piping projects in ABS, PVCC & Polybutane. Repairs, protection and reclamation of industrial equipment and surfaces are an additional service provided using a wide range of superior products and services.

Contact the Operations Manager on (03) 6265 2882






Contact Global Poly Water Tanks

Phone: (03) 6265 2882

13 Oaks Court Sorell Tasmania 7172 PO Box 36 Sorell Tasmania 7172 Fax: (03) 6265 1006

Email: sales@globalcontract.com.au





- Polyethylene Welding & Fabrication
- Aquaculture Sea Cages & Equipment
- Industrial and Water Storage Tanks
- Industrial Coatings & Refurbishments








AVAILABLE FROM



Site Preparation: Firm level foundations are required, clear of sharp projections. Sand bedding of 100mm depth should be used, build up of backfill around the tank is not required. Overflow should be piped away from the foundation where the soil is likely to erode. Straight sided tank walls allow the weight to be distributed over the largest possible area. The polyethylene is sufficiently elastic to enable it to conform to the change in ground shape without damage to the tank. Foundation instructions must be adhered to or warranty is void. The tank is not designed to be buried and is done at the owner's um tank distance from walls or structures is 120mm. Dome Tops: These are not designed to walk on and doing so could cause the lid to dent in. Do not allow children to play on lids. Care should be taken to make sure you have a suitable surface to collect rainwater for drinking. All specifications are approximate and subject to change. Global reserves the right to modify or change thei products without notice. The Written Warranty is limited to one owner, one site location, becoming void upon re-sale or movement to another site. Care should be taken to make sure you have a suitable surface to collect rainwater for drinking. Global Poly Tanks are warranted to the original purchaser to be free of defects in material and workmanship for the specified period from the date of purchase. The warranty is strictly limited to making good at the Global factory with freight prepaid. The tank colour may fade over time. Any fading is not covered by this warranty. The reproduction of product colours shown here, is as close as the photographic and commercial printing processes allow. Manufactured by Global Contract Services, 13-17 Oaks Court, Sorell, Tasmania, 7172. ACN 009 589 931





- Global Poly Tanks
- Rain Harvesting Products
- Pumps & Pump Covers
- Septic Tanks

10 Good Reasons to choose a Global Poly Water Tank

...to Harvest your Rainwater

- 1. Tasmanian Owned and Manufactured
- 2. 12 Year Warranty
- 3. Easy to Install
- 4. State-wide Delivery
- 5. Range of Colours and Sizes
- 6. Friendly and Professional Staff
- 7. Superior Seamless Construction
- 8. Manufactured from Food Grade Polyethylene
- 9. Resistant to Chemicals, Corrosion, Rusting or Rotting
- 10. Quality Assurance Certification AS/NZS ISO 9001:2008





700 Litres (155 Gallons) 1500mm Height Diameter 820mm Inlet height 1500mm Price inc GST



1200 Litres SIZE (265 Gallons) Height 1270mm Diameter 1100mm Inlet height 1250mm Price inc GST



1300 Litres SIZE (290 Gallons) 1670mm Height

Diameter 1100mm Inlet height 1650mm

Price inc GST



Slimline 1800 Litres SIZE

(400 Gallons) 2030mm Height Width 1500mm Depth 950mm Inlet height 2020mm

Price inc GST

SIZE



2300 Litres

(510 Gallons) 1400mm Diameter 1450mm Inlet height 1350mm

Price inc GST



5000 Litres SIZE (1100 Gallons)

1870mm Height Diameter 1890mm Inlet height 1780mm



6300 Litres

(1400 Gallons) 1740mm Height Diameter 2310mm Inlet height 1680mm

Price inc GST



11925 Litres

(2650 Gallons) 2800mm Diameter 2310mm

Inlet height 2680mm Price inc GST



14409 Litres

(3200 Gallons) 1960mm

Height Diameter 3400mm Inlet height 1760mm

Price inc GST

SIZE



22700 Litres SIZE

(5000 Gallons) Height 2720mm

Diameter 3400mm Inlet height 2530mm

Price inc GST



Price inc GST

10150 Litres

(2250 Gallons)


Height 2590mm Diameter 2310mm Inlet height 2425mm Price inc GST

Round Water Trough



300 Litres SIZE (66 Gallons) Height 420mm Diameter 1050mm

Price inc GST



Price inc GST

1150mm

Price inc GST

\$



550mm

Price inc GST



Height 575mm Length 600mm



700 Litres SIZE (155 Gallons) Height 540mm Width 920mm Length 1930mm Price inc GST

Global Poly Tanks include

- 1" or 1½" Brass Outlet & Gate Valve
- 75mm or 90mm Overflow optional on smaller tanks
- Leaf Strainer
- Mosquito Strainer
- Standard or Special Fit-out of Overflow and Outlet Positions
- 5V 64mm Fire Fighting Fitting additional charge
- Domed or Scew Lid additional charge



YANK Septic Tank 900 Litres

• Designed and manufactured in Tasmania to comply (200 Gallons) with AS/NZS 1546.1:1998

• Rotationally moulded from UV Resistant polyethylene

• No in site assembly of inlet or outlet connections

• No hold down attachments required

- No lid or baffle to fit
- Installation instructions provided



3085 Litres SIZE (685 Gallons)

Height 1400mm 1700mm Width Length 2200mm

Price inc GST