

AUPP00033 Porter's Paints Matt Wall Sealer

Introduction

Part A
PZ5-D0845

Description and Image

Porter's Matt Wall Sealer is a water based clear sealer for use with Porter's Interno and Smooth Impasto. Matt Wall Sealer is a clear protective sealer that allows these matt decorative finishes able to resist marking and staining and makes them wipeable.

Features and Benefits

- Allows the stated surfaces to resist marking and staining, makes these matt decorative finishes wipeable.
- Waterbased

Uses

Interior use only.

Porter's Matt Wall Sealer is a water based clear sealer for use with Porter's Interno and Smooth Impasto.

✓ **Interior**

Precautions and Limitations

Do not apply in high humidity, below 10°C or above 30°C. Allow paints to cure for a minimum of 7 days before application. Over saturation whilst applying Matt Wall Sealer, or a substrate which is not completely dry, may cause white markings to appear on a surface. Avoid dribbles or runs as these will remain evident when dry. Test before use as a slight colour variation may occur.

Typical Properties

Colour

Appears milky white in can, dries clear.

Components

1

Number of Coats

2

V.O.C. Level

< 10 g/L

Touch Dry

2 hour (at 25 Deg C and 50% relative Humidity)

Clean Up



Water

Clean Up Description

Clean brushes and equipment with water. Do not pour paint down the drain. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Please confirm local requirements. For more information on responsible disposal of paint and packaging visit paintback.com.au or painttakeback.co.nz.

Application Methods



Brush

Apply two coats by brush in a random or "crows feet" method.

Application Conditions

Solids by Volume

17.23

Min

Max

Recommended

Wet Film Per Coat (microns)

67

Dry Film Per Coat (microns)

12

Recoat Time (min/hours)

6 hours

Theoretical Spread Rate (m²/L)

15

Application Guide

Surface Preparation

Apply Porter's Interno or Porter's Smooth Impasto according to specification. Surface should be clean and dry. Allow Interno and Smooth Impasto to cure for a minimum of 7 days before application.

Application Procedure and Equipment

Do not apply paint if Relative Humidity is above 85% or temperature is within 3°C of Dew Point.

Do not apply if the surface temperature is greater than 30°C or below 10°C, or likely to fall below 10°C during the application or drying period.

Stir thoroughly prior to use. Apply two coats by brush in a random or 'crow's feet' method, cutting in progressively. Important: Over-saturation whilst applying Matt Wall Sealer, or a substrate which is not completely dry, may cause whitish markings to appear on surface.

Avoid dribbles or runs as these will remain evident when dry.

Touch dry in 2 hours. Allow minimum 6 hours dry time between coats. Allow to dry 6 hours.

Health and Safety

SDS Number

DLXGHSEN001332

SDS Link

[View SDS Link](#)

Using Safety Precautions

Keep out of reach of children. waterproof gloves and safety glasses. Use only in well ventilated areas. Wash hands after use.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

PZ5-D0845

Size:

1 litre, 4 litre & 15 litre

Weight:

1.2 Kg, 4.6Kg, 16.4 Kg

Flash Point

NA

UN Number

NA

Dangerous Goods Class

Not classified as Dangerous Goods for transport by Road & Rail and Marine, Not classified as Dangerous Goods for transport by Air.

Package Group

NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.