



Make savings appear out of thin air with a Midea heat pump



**Heat Pump Selection** 

**HP170** 

170L Capacity

No. of Persons	Cold	Climate Warm	Hot	
ŤŤ	170	170	170	
ŤŤŤ	280	170/280	170	
iiii	280	170/280	170/280	
iiiii	-	280	280	
*****	-	280	280	
To be used as a guide only				

**HP280** 

280L Capacity



## **Smart Technology**

With a Midea heat pump, set up and operation monitoring is made simple thanks to an amazing, in built user-friendly controller.

### Operational modes

ECO (Heat Pump Only) mode: The standard mode where the highest efficiency is achieved

**Hybrid Mode:** The Heat Pump & E-heater operate together to ensure the set temperature is achieved

**E-Heater:** When the air temperature drops to below 5°C, the heat pump will automatically select E-heater mode for an electric hot water boost

**EVAPORATOR** 

# **Features**



Modern & Stylish A stylish slim line single piece unit incorporates a top-mounted compressor

with compact footprint



**Highly Efficient** more heat energy than the power input; saving on purchased energy



Wide Operating Range Operates as low as 5°C in ECO mode & between -20°C & 45°C with

additional E-heat boost



HP170

Tank-Wrapped Condenser Coil For efficient heat transfer & preventing water



Low Operating Noise Operating at a very low 48 dBA you will hardly



energy<sup>1</sup> than a conventional water heater, whilst providing reliable hot water all day and night.

Harvest the free energy from our plentiful air to

heat your water with the advanced Midea heat pump from Chromagen. This renewable energy

water heating technology uses up to 65% less



**Handy Controller** operation & helpful functions such as temp setting, timer & safety lock



**Built in Frost** Protection Protecting the condenser from icing for complete neace of mind



Auto Disinfection<sup>^</sup> Periodically heating the water beyond its set temp to prevent the growth of bacteria and legionella



Vacation Mode<sup>^</sup> Conserving energy while the heat pump is idle, and automatically reactivates prior to your return



Power Outage Memory Settings are retained outage

# in the event of a power

Smart Technology




Did you know?

only convert 1 kW of input power into a maximum of 1 kW of output heat.

# **Energy Efficiency**

Did you know?

Water heating accounts for nearly a quarter of the energy use and greenhouse gas emissions in the average Australian home.



\*Estimation based on HP280 (RSJ-35/300RDN3) STC's in Zone 3 under medium load, obtained from independent laboratory test results and followed by TRNSYS modelling and a retail electricity cost of \$0.30c per kWh.

An energy efficient hot water system such as the Midea heat pump is a great way for households to make substantial reductions in their energy consumption and cost of

A heat pump provides a quick and easy replacement of your old energy-hungry electric water heater, whilst also reducing CO<sub>2</sub> emissions by over 4 tonnes, and saving you up to \$930\* per year.

### **How it Works**

- 1. A fan draws in air, containing heat energy, across the evaporator
- 2. The evaporator turns the liquid refrigerant into a gas
- 3. The compressor pressurises the refrigerant into a hot gas
- 4. The hot gas inside the condenser coil heats the water inside the coil-wrapped tank
- 5. The refrigerant reverts back to a liquid after heating the water and continues to the evaporator for the process to start again



Energy use reduction based on CER (AS/NZS 4234) modelling, in Zone 3.2 Average COP is 3.72 based on AS/NZS 5125 test condition 2. Applicable to HP170 model only. Applicable to HP280 model only. Images indicative only - Actual product configuration may differ

# **Product Specifications**





Heat Pump Model	HP170	HP280
Nominal volume capacity (L)	170	280
Voltage / Hz / Phase	220-240 / 50 / 1	220-240 / 50 / 1
Element input power (W)	2150	3000
Heating capacity - Heat Pump Only (W)	1500	3000
Max water temperature (°C)	65	60
Max rated input power (W) / current (A)	2780 / 12.1	4300 / 18.7
Relief valve pressure (kPa)	1000	1000
Noise level (dBA)	48	48
Net Weight (kg)	90	145
Pipe connection diameter (mm)	DN20	DN20
Cylinder Type	Vitreous Enamel	Vitreous Enamel
Outdoor resistance class	IP24	IP24
Operating Mode Function	Manual	Automatic
Refrigerant type/quantity	R134a / 0.8kg	R134a / 1.2kg







# **Residential Warranty**

5 Year
Tank Cylinder
(3 Year Labour)

3 Year Compressor (1 Year Labour) 1 Year Electronics, Parts & Labour



# Why choose Chromagen?

- o A leading provider of solar energy solutions with over 50 years history
- o Offices Australia wide with a national dealer & service network
- A wide range of energy efficient solutions to suit your lifestyle
- o Committed to quality, innovation & energy-efficient solutions



chromagen.com.au | 1300 367 565

Solar Water Heaters | Continuous Flow Water Heaters | Heat Pump Water Heaters | Solar Power Systems