

White Out Film

Interior

SolarZone White Out privacy film is ideal for hiding unattractive views or for disguising features that spoil the external appearance of glass-fronted buildings.

OPTICAL & SOLAR PROPERTIES	Single Pane	Double Pane
Visible Light Transmitted	10 %	10 %
Visible Light Reflected (Int)		
Visible Light Reflected (Ext)	48 %	50 %
Ultra Violet Block	99 %	99 %
Total Solar Energy Reflected	36 %	34 %
Total Solar Energy Transmitted	17 %	15 %
Total Solar Energy Absorbed	47 %	51 %
Emissivity (Room Side)	0.90	0.90
Glare Reduction	89 %	89 %
Shading Coefficient	0.37	0.49
Solar Heat Gain Coeff. (G-Value)	0.31	0.42
U-Value Winter (IP)	1.07	0.49
U-Value Winter (SI)	6.08	2.78
Luminous Efficacy	0.27	0.19
Total Solar Energy Rejected	69 %	58 %

Window Shield Australia | www.windowshield.com.au
info@windowshield.com.au | T: 08 8350 9711
2/46 Byre Ave, Somerton Park SA 5044



WINDOW SHIELD
AUSTRALIA
The Window Film Professionals



White Out Film

Energy Efficiency

Specialty