



• L210A/C Series

Specifications		L210A	L210MA	L210C
MAX.Swing	mm(in)	Ø550 (21.7)	Ø550 (21.7)	Ø550 (21.7)
MAX.Turning Length	mm(in)	410 (16.1)	295 (11.6)	400 (15.7)
Standard Chuck Size	inch	8"	8"	10"
Bar Capacity	mm(in)	Ø65 (2.56")	Ø65 (2.56")	Ø80 (3.15")
Spindle Speed	r/min	4,000	4,000	3,000
Motor Power	kW(HP)	15/11 (20/15)	15/11 (20/15)	15/11 (20/15)
Travel(X/Z)	mm(in)	210/430 (8.3"/16.9")	220/400 (8.7"/15.7")	210/430 (8.3"/16.9")
Rapid Traverse	m/min(ipm)	36/36 (1,417/1,417)	36/36 (1,417/1,417)	36/36 (1,417/1,417)



• L210LA/LMA/LMAS, L230LMSA

Specifications		L210LA	L210LMA	L210LMAS	L230LMSA
MAX.Swing	mm(in)	Ø550 (21.7)	Ø550 (21.7)	Ø550 (21.7)	Ø550 (21.7)
MAX.Turning Length	mm(in)	530 (20.9")	530 (20.9")	530 (20.9")	517 (20.3")
Standard Chuck Size	inch	8"	8"	8"+5"	8"+6"
Bar Capacity	mm(in)	Ø65 (2.56")	Ø65 (2.56")	Main: Ø65(2.56") Sub: Ø33(1.29")	Ø65/Ø43 (2.56"/1.69")
Spindle Speed	r/min	4,000	4,000	Main: 4,000 Sub: 6,000	4,000/5,000
Motor Power	kW(HP)	15/11 (20/15)	15/11 (20/15)	Main: 15/11 (20.1/14.7) Sub: 3.7/2.2 (5/3)	15/11 (20/15)
Travel(X/Z)	mm(in)	210/550 (8.3"/21.6")	210/550 (8.3"/21.6")	210/550/750 (8.3"/21.6"/29.5")	210/555 (8.3"/21.9")
Rapid Traverse	m/min(ipm)	36/36 (1,417/1,417)	36/36 (1,417/1,417)	36/36/30 (1,417/1,417/1,181)	36/36 (1,417/1,417)



• L280 Series

Specifications		L280	L280L	L280LM
MAX.Swing	mm(in)	Ø590 (23.2")	Ø590 (23.2")	Ø650 (25.6")
MAX.Turning Length	mm(in)	720 (28.4")	1,070 (42.1")	1,000 (39.4")
Standard Chuck Size	inch	10"	10"	10"
Bar Capacity	mm(in)	Ø76 (2.99")	Ø76 (2.99")	Ø76 (2.99")
Spindle Speed	r/min	3,000	3,000	3,500
Motor Power	kW(HP)	22/18.5 (30/25)	22/18.5 (30/25)	22/18.5 (30/25)
Travel(X/Z)	mm(in)	220/750 (8.7"/29.5")	220/1,100 (8.7"/43.3")	220/1,020 (8.7"/40.2")
Rapid Traverse	m/min(ipm)	20/24 (787/945)	20/24 (787/945)	20/24 (787/945)