



HALITRAX TYRES®

TYRES FOR THE LONG HAUL

RADIAL L3/E3

HALITRAX RADIAL HR25 L3/E3

FEATURES

- ✓ Purpose built Radial OTR tyre.
- ✓ Extra durable cut & chip resistant compound.
- ✓ Heavy duty casing with reinforced side wall.
- ✓ Quality radial construction for superior performance.

BENEFITS

- ✓ Radial construction increases life span.
- ✓ High traction levels and long service.
- ✓ Industry leading performance in the harshest conditions.
- ✓ Low cost per hour benefits with proven results.



TECHNICAL SPECIFICATIONS

TYRE SIZE	STAR RATING	TREAD PATTERN	TRA CODE	LOAD @10KM/H	LOAD @ 50KM/H	RIM SIZE	OVERALL DIAMETER	SECTION WIDTH	PRESSURE @ 10KM/H	PRESSURE @ 50KM/H	TREAD DEPTH
17.5R25	**	HR25	L3/E3	182A2	167B	14.00/1.5	1348mm	445mm	650kpa	500kpa	27mm
20.5R25	**	HR25	L3/E3	193A2	177B	17.00/2.0	1493mm	521mm	650kpa	500kpa	32mm
23.5R25	**	HR25	L3/E3	201A2	185B	19.50/2.5	1617mm	597mm	650kpa	500kpa	35mm
26.5R25	**	HR25	L3/E3	209A2	193B	22.00/3.0	1750mm	673mm	650kpa	500kpa	40mm
29.5R25	**	HR25	L3/E3	216A2	200B	25.00/3.5	1874mm	749mm	650kpa	500kpa	41mm

Specialised Tyre & Rubber Repairers



WHYALLA - Ph: 08 8645 0444
KING ST, WHYALLA
SOUTH AUSTRALIA, 5600

WINGFIELD - Ph: 08 8243 2011
25 CLYDE ST, WINGFIELD
SOUTH AUSTRALIA, 5013