- With or without concrete roof
- Proven for 50 years
- Concrete is poured in one operation
- Guaranteed against leakage for 10 years*
- All concrete used, minimum 32 MPA
- All tanks are fully vibrated and reinforced

For a once only investment your on-going water cost will be considerably reduced.

water...

is vital in Australia and periodic dry seasons emphasize the importance of an adequate conservation project on every property!

We manufacture tanks to meet Australian Standards AS3735 and can put a Quality Assurance System in place if required.


Terms of Payment - Settlement 7 Days

	Amount of water caught from Annual Rainfall in litres											
ROOF AREA m²	400mm	500mm	600mm	700mm	800mm	900mm	1000mm	1100mm	1200mm			
50	20,000	25,000	30,000	35,000	40,000	45,000	50,000	55,000	60,000			
100	40,000	50,000	60,000	70,000	80,000	90,000	100,000	110,000	120,000			
150	60,000	75,000	90,000	105,000	120,000	135,000	150,000	165,000	180,000			
200	80,000	100,000	120,000	140,000	160,000	180,000	200,000	220,000	240,000			
250	100,000	125,000	150,000	175,000	200,000	225,000	250,000	275,000	300,000			
300	120,000	150,000	180,000	210,000	240,000	270,000	300,000	330,000	360,000			
350	140,000	175,000	210,000	245,000	280,000	315,000	350,000	385,000	420,000			
400	160,000	200,000	240,000	280,000	320,000	360,000	400,000	440,000	480,000			
450	180,000	225,000	270,000	315,000	360,000	405,000	450,000	495,000	540,000			
500	200,000	250,000	300,000	350,000	400,000	450,000	500,000	550,000	600,000			
	BLACKALL BOLLON ST GEORGE	MOREE ROMA WEE WAA	EMERALD INGLEWOOD CLIFTON TAMWORTH WARIALDA	DALBY PITTSWORTH GREENMOUNT KINGAROY	INVERELL GATTON CROWS NEST STANTHORPE	TOOWOOMBA ESK GLEN INNES ARMIDALE	TENTERFIELD BUNDABERG CABOOLTURE	BRISBANE	BEAUDESERT KILCOY CALOUNDRA			

Quotes exclude site preparation cost and site maintenance.

manner but confirm that our guarantee is subject to adequate site preparation. It is the purchaser's responsibility to conduct soil tests and arrange an Engineer's report if considered necessary and to attend to preparation of a site which is level with adequate

verification of a minimum surface compaction of 95%. Modified compaction to AS1298 and a minimum allowable bearing capacity of 100kPa. Adequate site drainage is to be maintained during construction.



TOOWOOMBA CONCRETE TANKS PTY LTD

1135 Ruthven Street, TOOWOOMBA Q. 4350 email: admin@twbaconcretetanks.com.au

Contact Harko Ellen

Phone: (07) 4630 9555

Mobile: 0458 063 630 or 0429 063 630 email: harko@twbaconcretetanks.com.au





















www.twbaconcretetanks.com.au



water...

One of our most valuable resources.

TCT

TOOWOOMBA
CONCRETE
TANKS PTY LTD

Our Concrete Tanks are designed to suit almost any application, large or small.

We have an extensive range of sizes available and we are also able to custom build to suit your particular need.

DOMESTIC

Concrete Tanks:

- water can be used during restrictions
- enjoy reduced council water rates
- insulated against heat, light and algae
- inground tanks provide additional useable outdoor space BBQ area!
- fire and vandal proof





EVERY DROP COUNTS

TANK SIZE	TROUGH	These measurements are approximate and will vary depending on final applicatio												
	4000litre	5,400ltr	13,500ltr	22,500ltr	27,000ltr	34,000ltr	45,000ltr	52,000ltr	95,000ltr	144,000ltr	400,000ltr	500,000ltr	600,000ltr	700,000ltr
	900gal	l 200gal	3000gal	5000gal	6000gal	7500gal	10,000gal	11,500gal	21,000gal	32,000gal	90,000gal	III,000gal	133,000gal	155,000gal
Outside diameter	2,700mm	2,000mm	3,250mm	3,900 _{mm}	4,300 _{mm}	5,100mm	5,700mm	5,730 _{mm}	7,800 _{mm}	9,500mm	15,600mm	15,700mm	15,700mm	15,700mm
	9' feet	6'8"	10'4"	I3ft	14'4"	I7ft	I9ft	19'1"	26ft	31'8"	52ft	52'4"	52'4"	52'4"
Outside height	760 _{mm}	2,450mn	2,400mm	2,250mm	2,550mm	2,400mm	2,250mm	2,550mm	2,550mm	2,550mm	2,650mm	3,050mm	3,600mm	4,152mm
	2'6"	8'2"	8ft	7'6"	8'6"	8ft	7'6"	8'6"	8'6"	8'6"	8'10"	10'2"	I 2ft	13'10"

RURAL

Concrete Tanks for:


- stock tanks and troughs
- piggeries and flush tanks
- feed lot water storage
- concrete roof requires no maintenaince ever

INDUSTRIAL

Concrete Tanks for:

- sewage treatment
- overflow tanks
- water skimmer tanks
- compartment and cone tanks
- town water supplies for small towns and communities





GALLONS





We will build inground tanks with roof loading from non-trafficable to capable of carrying a semi trailer. Up to 2 metres fill over roof.